

911022 LUISIANA SUPERELASTIC

PVC 软管, 硬质 PVC 筋骨螺旋, 用于抽吸和输送液体。

PVC hose with rigid PVC spiral, for delivery and suction of liquids.



商品详情

表面平滑度

SMOOTH SURFACE

柔韧性能

FLEXIBILITY

耐磨性能

ABRASION RESISTANCE

适用温度范围

TEMPERATURE RANGE

-25°C + 55°C

抗化学物质

CHEMICAL RESISTANCE

tabella PVC

抗压性能

CRUSHING RESISTANCE

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
	20	26.2	275	65	6.5	21	7	50
1	25	31.6	330	100	6.5	21	7	50
	30	37	420	125	5.5	18	7	50
1 1/4	32	39.2	460	135	5.5	18	7	50
	35	41.8	500	145	5	16.5	7	50
1 1/2	38	45.4	550	155	4.5	15	7	50
	40	47.8	610	160	4.5	15	7	50
1 3/4	45	52.8	670	180	4	13.5	7	50
2	50	58.2	810	200	3.5	12	7	50
	60	69	970	245	3.5	12	v	50
2	63	71.5	1040	260	3.5	12	7	50

1/2								
	75	85.4	1380	315	2.5	9	7	50
	76	86.2	1380	320	2.5	9	7	25
	80	90.6	1560	325	2.5	9	7	25
4	102	114	2160	430	2.5	9	7	25
5	127	146	3130	670	2	7.5	5	25
6	152	167.2	4250	750	2	7.5	5	25