

HT1000



应用 APPLICATION

用于汽车废气排放系统、汽车尾气回收：软管卷盘，地面开槽通道，地下回收系统；高温抽吸：陶瓷工业、玻璃工业；波纹管，补偿器。

Used for automotive exhaust emission systems and automotive exhaust gas recovery: hose reels, ground slotted channels, underground recovery systems; High temperature suction: ceramic industry, glass industry; Bellows, compensators.

特性 CHARACTERISTIC

良好的耐热性能；通过外部夹型形成耐磨保护，阻燃依据DIN4102-B1。

Good heat resistance performance; Wear resistant protection is formed through external clamping, and flame retardant according to DIN4102-B1.

温度 TEMPERATURE

约-60°C至+900°C；短时间可达到约+1100°C。

Approximately -60 °C to +900 °C; It can reach about +1100 °C in a short period of time.

结构 STRUCTURE

卡箍螺纹，镀锌钢；管壁采用不锈钢螺旋丝加强，玻璃纤维织物特殊涂层。

Clamp thread, galvanized steel; The pipe wall is reinforced with stainless steel spiral wire and coated with special fiberglass fabric.



内径 (mm)	外径 (mm)	弯曲半径 (mm)	真空度 (bar)	重量 (kg/m)	长度 (m)
Inside diameter	Outside diameter	Bending radius	Vacuum	Weight	Standard length
100-102	114	64	0.180	2.800	6
110	124	69	0.160	3.050	3 6
114-115	129	72	0.150	3.180	3 6
120	134	74	0.140	3.310	3 6
125-127	139	77	0.120	3.430	3 6
130	144	79	0.110	3.560	3 6
140	154	84	0.090	3.820	3 6
150-152	164	89	0.075	3.070	3 6
160	174	94	0.070	3.270	3 6
165	179	97	0.065	3.370	3 6
170	184	99	0.065	3.460	3 6
175	189	102	0.060	3.550	3 6
178-180	194	104	0.055	3.650	3 6
200-203	214	114	0.045	4.030	3 6
215	229	122	0.040	4.320	3 6
225	239	127	0.040	4.510	3 6
228-229	242	129	0.035	4.590	3 6
250	264	139	0.035	4.990	3 6
254	268	141	0.030	5.070	3 6
275	289	152	0.030	5.470	3 6
280	294	154	0.025	5.570	3 6
300	314	164	0.025	5.950	3 6
305	319	167	0.025	6.020	3 6
315	329	172	0.025	6.150	3 6
325	339	177	0.015	6.550	3 6
330	344	179	0.015	6.630	3 6
350	364	189	0.015	6.910	3 6
356	370	192	0.015	7.000	3 6
375	389	202	0.015	7.250	3 6
400	414	214	0.010	7.870	3 6
405-406	420	217	0.010	7.990	3 6
450	464	239	0.010	8.830	3 6
457	471	243	0.010	8.960	3 6
500	514	264	0.010	9.790	3 6
508	522	270	0.010	9.940	3 6