

YP101



应用 APPLICATION

用于牙科器具和医疗器具的专用管，也可用作线缆保护管。

The product can be used as dental and medical special hose as well as ordinary cable protection hose.

结构 STRUCTURE

双层管壁，轻且弯曲非常灵活的PVC软管，内外壁平滑，两个PP丝螺旋加强且轴向有纱线进行加强。

Double layers of hose wall, with light and very flexible bending PVC hose. The hose's outer and inner walls are both very smooth, and it is double PP wire screw and axial yarn reinforced.

温度 TEMPERATURE

0°C至+40°C (短时间内可达+60°C)

0 °C to +40 °C (up to +60 °C in a short period of time)

可选颜色 OPTIONAL COLORS

黑色/灰色/白色

Black/Grey/White



内径 (mm) Inside diameter	外径 (mm) Outside diameter	弯曲半径 (mm) Bending radius	真空度 (bar) Vacuum	重量 (kg/m) Weight	长度 (m) Standard length
6.0	10.0	10	250	0.040	50
8.0	12.0	15	250	0.050	50
10.0	14.0	18	250	0.060	50
10.5	14.5	18	200	0.062	50
11.0	15.0	19	200	0.070	50
12.0	16.0	20	200	0.073	50
12.5	16.5	20	200	0.075	50
14.0	18.0	24	200	0.080	50
15.0	19.0	25	200	0.090	50
16.0	20.0	27	200	0.098	50
17.5	21.0	30	200	0.108	50
19.0	23.0	32	200	0.113	25
20.0	24.5	33	200	0.117	25
20.5	25.0	33	200	0.119	25
21.0	25.5	34	200	0.121	25
21.5	26.0	34	200	0.123	25
22.0	27.0	35	200	0.125	25
25.0	30.0	40	200	0.150	25